

**ARKEMA**

Orlane BOUZARD

**IMPROVE THE SUSTAINABILITY AND PERFORMANCE OF YOUR REACTIVE SYSTEMS USING POLYAMIDE WAXES RHEOLOGY MODIFIERS**Abstract:

Rheology modifiers are key ingredients to reach the ever more demanding performance standards of many adhesives and sealants systems including ease of application combined with structure development. Such additives are helping adhesives & sealants manufacturers in meeting existing and future challenges in many areas. For example, the construction market is requiring higher load-bearing capacity with the rise of high tack systems. The importance of bio-based raw materials is not to be undermined either in today's world. This is why polyamide-based rheology modifiers are not only high-performance additives but also stand for sustainable additive solutions.

Polyamide rheology modifiers are established as leading additives for enhanced applicative control in Silylated Terminated Polymer (STP), compared to other technologies such as fumed silicas or precipitated calcium carbonates. Other reactive technologies can also benefit from their better structure control, for example: 2K-Epoxies, 2K-PU, acrylates.

After introducing the Polyamide Rheology Modifiers technology, their benefits in each relevant system will be described. This presentation will highlight the innovation in STP systems, adapting to the current challenges: shortening cycle times, enhancing tack. It will then demonstrate how such additives can be interesting in other reactive systems focusing on rheological behavior using different characterization methods. Finally, an overview of the sustainability aspect of these additives will be presented.

**Bostik**

N.N.

**TBA**Abstract:

Coming soon!

**Cardolite Specialty Chemicals Europe**

Tom Berckmans

**NOVEL CASHEW NUT SHELL LIQUID BASED ISOCYANATE BLOCKING AGENT FOR LOWER DEBLOCKING TEMPERATURE**Abstract:

Cashew Nut Shell Liquid (CNSL) is a non-edible natural oil obtained as a by-product of the Cashew nut industry. CNSL is used as building block for materials used in epoxy coatings, adhesives, composites and PU Foam. Its unique chemical backbone improves chemical resistance, hydrophobicity, and thermal properties.

NX-2026™ (3-pentadeca-dienyl-phenol) is a very high purity cardanol, derived from Cashew Nutshell Liquid. Once used in polyurethane prepolymers as an isocyanate blocking agent, it has demonstrated favorable and easily tunable deblocking conditions. Cardolite has already introduced tools i.e. catalysts, deblocking agents, to optimize and lower deblocking temperature of NX-2026 blocked isocyanates in a previous presentation.

In this paper, a novel cardanol-based fully cycloaliphatic derivative, called CNSL-Oxime, will be presented, investigating its use as innovative isocyanate protective group with faster reactivity and lower deblocking temperatures than petro-derived benchmarks, without compromising shelf-life of blocked systems nor affecting mechanical and thermal properties of epoxy-PU hybrid systems.

## Coatex (Arkema Group)

Dr Catherine CORFIAS-ZUCCALLI



### RHEOLOGICAL CHARACTERIZATION OF WATER-BASED THICK ADHESIVES

#### Abstract

How to ensure that a thick adhesive is easy to apply and holds up when bonding the substrates? What does it take for a correct adhesive application? The answer lies in optimizing rheological properties of systems to achieve the thickness and workability together with control of sag, hold up and creep of the wet adhesive. Control of its application is essential to ensure its final mechanical and adhesion properties.

The applicability of waterborne adhesives using a manual tool is very dependent on the ability of the adhesive to flow under stress. Thus, the rheological approach is relevant to physically describe the flow mode of these soft solid viscoelastic materials that need to be applied with a high, regular and homogeneous thickness on different substrates.

The objective is to identify the rheological parameters that best describe the applicability of these thick adhesives. We will compare various acrylic thickeners to illustrate these parameters.

These characterizations will be carried out in formulations comprising the essential ingredients to target the mechanical resistance of these thick adhesives, aiming at achieving correlations between viscoelastic behavior and application properties.

---

## Dynasol Group (Repsol)

Jesus Eduardo Ibarra



### NEW SEBS FOR HOT MELT ADHESIVES WITH LOW MELT VISCOSITY FOR INDUSTRIAL AND MEDICAL APPLICATIONS

#### Abstract

The incursion of SEBS hydrogenated copolymers in the adhesive market, until now has marked a trend in the market segments of sealants or translucent labels, this due to its excellent resistance to UV light, to the effects of the environment and its good resistance ozone and high temperature.

New SEBS hydrogenated copolymers have been developed, with the ability to give the Hot Melt adhesive an excellent low temperature processability, maintaining stability in adhesion properties at low temperature ( $\approx -5^{\circ}\text{C}$ ) and at temperatures above room temperature ( $\approx 60^{\circ}\text{C}$ ); allowing the adhesive to obtain low peeling strength for applications where it is imperative not to leave a residue on the substrate or not damage it, when the label, tape or film is removed, as is the case with labels or tapes for medical use with direct or indirect contact with the skin, as well as the protective paint films that are placed on new vehicles.

The design and structure of these SEBS make them feasible to be formulated with hydrogenated hydrocarbon resins, which by their nature have no color or odor, this being one of the main requirements in adhesives, with special applications that are in direct or indirectly contact with the skin, food or medicine.

The objective of this work is to show to adhesives market the feasibility of using these new SEBS with their operational and performance advantages.

---

## Fitech

Patrik Thoma



### AUTOMATION OF MIXING PROCESSES FOR ADHESIVES AND SEALANTS

#### Abstract

Coming soon!

---

## Fracture Analytics

Dr. Martin Brandtner-Hafner



### STRUCTURAL SAFETY EVALUATION OF ADHESIVE SEALANTS

#### Abstract

In the construction industry, adhesives and liquid sealants have become indispensable. The harsh conditions on-site often demand the highest performance from such products. Since adhesive applications and sealing solutions are often required in one product, so-called adhesive sealants are a tailored hybrid solution. The aim here is to combine the best of two worlds. However, information from the manufacturers' technical datasheets only provides a first rough overview of their lab performance. Likewise, missing key figures and a lack of empirical data often lead to confusion among practitioners and even end in faulty applications. The resulting damage often leads to financial if not legal problems. To avoid these, commercially available adhesive sealants were tested for their structural bonding suitability and compared with benchmarks from the industry. It was found that one chemical system is particularly highly suitable for both, bonding and sealing building materials, respectively. This gives the user the opportunity to select and optimally apply the ideal adhesive sealing system for his application.

#### **Keywords:**

Structural Safety Evaluation, Bonding Efficiency, Adhesive Sealants, Safety Zone, Sealant & Adhesive Factor.

---

## Fraunhofer Institute for Manufacturing Technology and Advanced Materials IFAM

Jonas Wirries



### PROPERTIES AND RELAXATION BEHAVIOUR OF CURING STRUCTURAL ADHESIVES

#### Abstract

During the process of adhesive curing, volume shrinkage occurs due to the cross-linking of the polymer chains. In interaction with the adhesion between components and adhesive and the change of properties, such as the increase in Young's modulus and the decreasing relaxation capacity, the curing shrinkage leads to formation of residual stresses in bonded joints. The prediction of these residual stresses has so far been limited to application-specific models and cannot be used generally. To enable a more global prediction, better knowledge of the relaxation behaviour is needed.

Based upon experimental results of the thermoanalytical characterisation of structural adhesives during cure, input data for FEA are generated. In addition, the effects of shrinkage and residual stresses on simple geometries are determined during adhesive curing. Furthermore, a method is developed to determine curing shrinkage under different stiffnesses of the joining partners. These findings will be combined to extend existing mechanical models to include relaxation behaviour and improve predictions of residual stresses.

---

## Fraunhofer Institute for Structural Durability and System Reliability LBF

Jens-David Wacker



### TBA

#### Abstract

Coming soon!

---

## Huntsman Advanced Materials

Simon Thering



### ARALDITE® ADHESIVE MATERIAL MODELS TO ACHIEVE ACCURATE APPLICATION SIMULATIONS LEADING TO A SHORTER QUALIFICATION TIME OF ADHESIVE INNOVATIONS

#### Abstract

While numerical simulation is widely recognized as a robust tool to assist design of adhesively bonded structures, its applicability relies on realistic data combined in a material model based on solid experimental characterization. Huntsman just recently launched its new realistic

adhesive material models that help adhesive users to achieve fast and accurate application simulations when qualifying adhesives. Based on solid experimental characterization, the adhesive material models provide a wealth of information about the physical, mechanical and thermal behaviour of the Huntsman adhesive core product range. The adhesive material model helps adhesive users to go to market faster and shorten qualification time by getting the data they need to predict the combined effect of design parameters and adhesive properties over the process and operational conditions of the customer's project.

This presentation is about presenting the new material model, showing how a simulation can help to shorten the qualification time by defining the fitting adhesive fast. A case study about the latest launched ARALDITE® 2080 two-component acrylic adhesive, will highlight how important a simulation is to qualify especially new innovative adhesives faster. ARALDITE® 2080 adhesive solves customer's issues that are related to currently used MMA or PU adhesives while being low odor, non-flammable, primer free and having good EHS values. Despite those, ARALDITE® 2080 adhesive provides high bond strength, elongation, flowability, and fast cure times.

---

## Loparex and Wacker Chemie

Ian Grace and Dr. Thomas Gröer



### THE FUTURE IS COLLABORATION RELEASE LINERS AND HIGH-PERFORMANCE SILICONE ADHESIVES, A VIEW FROM BOTH SIDES

#### Abstract Loparex

Release Liner choice is most often the very last part of any product design, and rightly so.

It is not possible to select the correct Release Liner until the Adhesive & Process have been defined.

Selecting the correct Release Liner for a Health Care application can bring added complexity, especially when it involves compatibility with the latest generation of Silicone PSA's.

Knowing how a Pressure Sensitive Adhesive performs with a specific Release Liner can reduce development time and consequently, time to market.

With the development of new Silicone PSA systems, the need for collaboration with the Adhesive producer has never been more relevant. We would like to present to you the basics of Release Technology, the special requirements for Silicone PSA's and some market demands that have led to a unique collaboration.

#### Abstract Wacker:

Advanced wound care, as many other applications in the medical field, where reliable yet sensitive adhesion and painless removal of wound dressings or tapes are imperative, have generated an increasingly strong demand on the adhesive properties of silicone medical gels.

Increasing adhesion does also go together with the necessity for release liners, which assure protection of the adhesives layer as well as an easy and stainless release. Be it in-process or for the final good.

We present the results of a unique collaboration, showing release force measurements and long-term studies on the suitability of commonly used groups of liner materials with high-performance medical silicone adhesives.

---

## Plasmatreat

Klaus Kresser



### PLASMAPLUS® - THE NEW TECHNOLOGY FOR SOLVENT FREE BONDING

#### Abstract

Why is it beneficial to dispense with solvents? Solvents are only auxiliary materials for processing coatings or adhesives. This means that for the actual function - such as adhesion, corrosion protection, etc. - they make no contribution. On the contrary, they make production processes more expensive, since useless material has to be transported, stored and processed. In addition, solvents often lead to tighter labeling of coatings or adhesives because they become harmful to health, hazardous to the environment or flammable.

Here, PlasmaPlus® coating simplifies the process. All different types of materials like plastic, glass, metal, aluminum, etc. can be coated with PlasmaPlus®. Plasma polymerization with the PlasmaPlus® process is

already being used successfully for surface coating in a large number of different industrial applications. Herewith PT-Bond coatings assure long-term adhesion.

In the paper, the following topics will be introduced and discussed:

- Distinction between different plasma technologies: Activation of surfaces and coating of surfaces via PECVD (Plasma Enhanced Chemical Vapor Deposition).
- Examples of substrate/adhesive combinations, where PECVD can be used for the replacement of primers.
- State of the Art solutions for solvent and flash-off free bonding processes and their technical and chemical background.
- Examples of successful implementation and industrialization of green processes and new materials with PECVD technology
- Examples Lean pre-treatment solutions for bonding are industrialized

---

## Schill+Seilacher "Struktol"

N.N.



**TBA**

**Abstract:**  
Coming soon!

---

## SKZ-German Plastics Center

Heinrich Leicht



### **ELECTROMAGNETIC SHIELDING OF CARBON-FILLED SILICONES**

**Abstract:**

New communication technologies (e. g. 5G), autonomous and electric driving as well as the internet of things and Smart Cities are just a few of the current technological trends. All these technologies have in common that their electronic components intentionally or unintentionally emit electromagnetic waves which might interfere with surrounding electronics. Furthermore, they are themselves susceptible to electromagnetic interferences (EMI) caused by their surroundings.

Thus, EMI shielding is necessary to ensure the proper operation of devices, which is especially important for applications with a high safety level (e. g. autonomous driving). Miniaturization (less space left for shielding) and lightweight construction (substitution of shielding metals with inherently non-shielding polymers) are making it harder to achieve the necessary shielding with common technologies and create a technological need to develop innovative materials to face these challenges.

Polymer composites with fillers that increase their EMI shielding might be one solution, which is evaluated in the currently running project carBONDshield (IGF-No. 21772 BG). The homogenous dispersing of these fillers into a polymeric matrix while maintaining the base material properties is one of the most substantial challenges.

The presentation will show how carbon-based fillers (e. g. carbon nanotubes, carbon black or carbon fibers) influence the EMI shielding performance as well as other material parameters (e. g. electrical conductivity, viscosity) of silicones.

---

## Technical University of Braunschweig / Institute of Joining and Welding

Elisabeth Stammen



**TBA**

Abstract  
Coming soon!